

G-170C RS 29ER

G-170 Gravity / Enduro Suspension - 170mm

SRP £3,799

Product Code - WG170CRS(size)V2



		Colour	Matt Olive with Burnt Orange / Khaki
		Sizes Available	S,M,L
		Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
✓	✓	Fork	RockShox Lyrik Select + RC 29", 160mm Travel, 42mm Offset, DebonAir, Charger 2 RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
✓	✓	Rear Shock	RockShox Super Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment
		Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
	✓	Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, Micro Engagement 6 Pawl, XD Driver, 32 Hole
✓		Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 31mm Torque Caps, 32 Hole
	✓	Spokes	DT Swiss Factory 2.0mm, Black Stainless, Brass Nipples
	✓	Rims	RaceFace AR-30, Offset, 30mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
✓	✓	Tyres	Maxxis Minion DHF WT, TR, 29" x 2.5" 60TPI, EXD Sidewall Protection, 3C Maxx Terra, Dual Compound, Folding Bead, Front, Maxxis Aggressor WT, TR, 29" x 2.5" 120TPI, Dual-ply Enduro casing with Butyl Inserts, Dual Compound, Rear
✓		Shift Levers	SRAM GX Eagle, MMX, 12 Speed
		Front Derailleur	N/A
✓		Rear Derailleur	SRAM GX Eagle, 12 Speed
	✓	Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
		Chain	SRAM Eagle, 12 Speed
	✓	Crankset	SRAM Descendant 7K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
		Bottom Bracket	SRAM DUB, BSA, 73mm
✓	✓	Seatpost	Bike Yoke Divine, 30.9mm, S 125mm Travel, M/L/XL 160mm Travel, Trigger Remote with MMX attachment
		Seat	Whyte Custom, Dual Density, Triple Panel Design
		Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
✓		Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
		Grips	Whyte Lock-on V Grip
	✓	Front Brakes	SRAM Code R, 4 Pot with Sintered Metal Pads, 200mm Rotor
	✓	Rear Brakes	SRAM Code R, 4 Pot with Sintered Metal Pads, 200mm Rotor, Internal Routing
	✓	Brake Levers	SRAM Code R, MMX
		Pedals	None
✓		Indicates an upgrade or improvement over previous version	
✓	✓	Indicates an upgrade or improvement over the model below	

The RS uses the same highly developed frame as the Works bike, as used by our International EWS race team. The 29er wheels make this the fastest Gravity bike we've ever created.

This bike is ready for anything you want to throw at it, from hard-core trail riding to EWS Enduro racing. With its open front triangle design it is possible to fit various options of rear shock including coil shocks and still carry a full size water bottle.

The G-170 platform is designed around the Whyte's performance-enhancing Optimised Trail Offset geometry which also features the most compact seat-tubes possible on all sizes - meaning riders can choose the size with the reach they prefer, and simply adjust the seat-post to fit.

Dropout Code	DROPWH18
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.3	75	585	349	840
M	64.3	75	604	349	844
L	64.3	75	629	349	869
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1205	435	30.9	110	406.4
M	1225	435	30.9	120	431.8
L	1250	435	30.9	130	457.2

G-170C RS 29ER

G-170 Gravity / Enduro Suspension - 170mm

SRP £3,799

Product Code - WG170CRS(size)V2

ADDITIONAL SPECIFICATION & REPLACEMENT PARTS

Top Tube	High Modulus Uni-Directional Carbon
Down Tube	High Modulus Uni-Directional Carbon
Rear Stays	6061 Alloy Double Butted
Paint Code	WAMTU016
Freehub Part Code	WHYFHUB19
Rear Hub Bearings	6903
Front Hub Bearings	6902
Suspension Bearings	WB0025 X 10
Headset Bearings	HS003 (FSA No42)
Headset Code	
Bottom Bracket	BSA SRAM DUB, 73mm
ISG Chainguide Compatibility	
ICR Grommets	1 x WHYICR18-3, 2 x WHYICR18-1
Brake Mount Adaptor	WHYFM200
Spoke Lengths	295 x 292mm (front) 293 x 292mm (rear)
Max Chain Ring Size	36T
Chain Length for the stock chainring	116
Tubeless Status	Tubeless Ready Rims
Max Tyre Size	29 x 2.8 Front / 29 X 2.6 Rear
Max Tyre Size with Mudguards	N/A
Mudguard Code	N/A
Rack Compatible	N/A
Kickstand Compatible	N/A
Chain Guide Code	WAMCG1
Rear Thru-Axle Length	M12 X 1.75, 182mm Long
Downtube Protector	WHYPRO11
Chainstay Protector	WHYPRO07
Seat Post Seal	WHYPOSTSEAL 3/4/5
Kitbox Contents	