## G-170 S

## G-170 Gravity / Enduro Suspension - 170mm

SRP £2,499

Product Code - WG170S(size)V2





		·	
	Colour	Matt Midnight with Red / Grey	
	Sizes Available	S,M,L,XL	
	Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts	
<b>✓</b>	Fork	RockShox Lyrik Select RC 27.5", 180mm Travel, 37mm Offset, DebonAir, Charger RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate	
<b>✓</b>	Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment	
	Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings	
	Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole	
<b>√</b>	Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 31mm Torque Caps, 32 Hole	
	Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples	
$\checkmark$	Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole	
<b>✓</b>	Tyres	WTB Vigilante TCS System 27.5" X 2.5" Light/High Grip, Tri-Tec triple compound, Slash Guard sidewall protection, Front, WTB Trail Boss G2 TCS System 27.5" X 2.4" Tough/Fast Rolling, Tri-Tec triple compound, Enduro Casing, Rear	
<b>√</b>	Shift Levers	SRAM SX Eagle, MMX, 12 Speed	
	Front Derailleur	N/A	
<b>√</b>	Rear Derailleur	SRAM SX Eagle, 12 Speed	
<b>√</b>	Cassette	SRAM PG-1210 Eagle, 11-50, 12 Speed	
	Chain	SRAM Eagle, 12 Speed	
	Crankset	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 30T, DUB, 170mm, Boost, 12 Speed	
	<b>Bottom Bracket</b>	SRAM DUB, BSA, 73mm	
<b>✓</b>	Seatpost	Whyte drop.it II Post, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Paddle Remote Lever	
	Seat	Whyte Custom, Dual Density, Triple Panel Design	
	Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide	
<b>√</b>	Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension	
	Grips	Whyte Lock-on V Grip	
<b>√</b>	Front Brakes	SRAM Guide GE, 4 Pot with Sintered Metal Pads, 200mm Rotor	
<b>√</b>	Rear Brakes	SRAM Guide GE, 4 Pot with Sintered Metal Pads, 200mm Rotor, Internal Routing	
<b>√</b>	Brake Levers	SRAM Guide GE, MMX	
	Pedals	None	
<b>√</b>	Indicates an upgrade or improvement over previous version		

Indicates an upgrade or improvement over the model below

The G-170 S scored the perfect 10 and was named Editor's Choice by MBR as well as being crowned Best Value MTB in the 2018 Pinkbike awards. Available in the UK from late June 2019, the v2 spec adds RockShox's new Lyric fork with a Charger 2 damper, an upgraded rear shock and improved brakes to the award-winning mix.

The v2 S is loaded with the very latest spec developments in Enduro/Trail bikes, like the new WTB ST i30mm 2.0 rims which further improve the performance of the front and rear specific TCS tyres, whilst maintaining neutral handling.

The G-170 platform is designed around the Whyte's performance-enhancing Optimised Trail Offset geometry which also features the most compact seat-tubes possible on all sizes - meaning riders can choose the size with the reach they prefer, and simply adjust the seat-post to fit.

Dropout Code	DROPWH18		
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)		
Reducer Bush Widths	22mm x 8mm, no hardware at the rear		
Eye to Eye Length	230mm		

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	75	583	337.5	840
М	64.5	75	603	337.5	844
L	64.5	75	628	337.5	869
XL	64.5	75	652	337.5	875
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1200	435	30.9	110	406.4
S M	1200 1221	435 435	30.9 30.9	110 120	406.4 431.8

G-170 S

G-170 Gravity / Enduro Suspension - 170mm

SRP £2,499

Product Code - WG170S(size)V2

## **ADDITIONAL SPECIFICATION & REPLACEMENT PARTS**

Top Tube	6061 Hydro Formed		
Down Tube	6061 Triple Butted Hydro Formed		
Rear Stays	6061 Alloy Double Butted		
Paint Code	WAMTU012		
Freehub Part Code	WHYFHUB07		
Rear Hub Bearings	6903		
Front Hub Bearings	6902		
Suspension Bearings	WB0025 X 10		
Headset Bearings	HS002 (FSA No57)		
Headset Code			
Bottom Bracket	BSA SRAM DUB, 73mm		
ISG Chainguide Compatibility			
ICR Grommets	1 x WHYICR04, 2 x WHYICR02		
Brake Mount Adaptor	WHYFM200		
Spoke Lengths	278 × 274mm (front) 294 × 292mm (rear)		
Max Chain Ring Size	36T		
Chain Length for the stock chainring	116		
Tubeless Status	Tubeless Ready Rims		
Max Tyre Size	27.5 X 2.8 Front / 27.5 X 2.6 Rear		
Max Tyre Size with Mudguards	N/A		
Mudguard Code	N/A		
Rack Compatible	N/A		
Kickstand Compatible	N/A		
Chain Guide Code	WAMCG1		
Rear Thru-Axle Length	M12 X 1.75, 182mm Long		
Downtube Protector	N/A		
Chainstay Protector	WHYPRO07		
Seat Post Seal	WHYPOSTSEAL		
Kitbox Contents			