

T-130 SR

T-130 Trail Suspension - 130mm

SRP £2,299

Product Code - WT130SR(size)V2



	Colour	Matt Petrol with Lime / Mist
	Sizes Available	XS,S,M,L,XL
	Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
	Fork	Fox Performance 34 27.5", 140mm Travel, 37mm Offset, GRIP 3-Pos Damper, Black Coating, Tapered Steerer, 110mm x 15mm Boost E-Thru Axle
	Rear Shock	Fox Float DPS, Performance, Black Coating, Rebound Adjustment and 3pos Adjust Evol LV
	Headset	FSA No. 57 Orbit ZS, ACB, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
	Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
	Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
	Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
✓	Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
	Tyres	Maxxis High Roller II TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.6" 60TPI, EXO Sidewall Protection, Rear
	Shift Levers	Shimano SLX M7000, I-Spec B, 11 Speed, Black
	Front Derailleur	N/A
	Rear Derailleur	Shimano SLX RD-M7000-SGS, Shadow Plus, Direct Mount, 11 Speed
	Cassette	SunRace CSM58, 11-46, 11 Speed
	Chain	Shimano HG601, 11 Speed
✓	Crankset	Whyte Forged 2pcs Cranks, Direct Mount 32T Narrow Wide Boost Chainring, 170mm, Boost, 11 Speed
	Bottom Bracket	BSA, Cartridge Bearings, 73mm
	Seatpost	Whyte drop.it II Post, 30.9mm, XS 100mm Travel, S 125mm Travel, M/L/XL 150mm Travel, Paddle Remote Lever
	Seat	Whyte Custom, Dual Density, Triple Panel Design
✓	Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, S 760mm Wide, 15mm Rise, M/L/XL 780mm Wide, 30mm Rise
	Stem	Whyte Gravity Stem, 35mm Extension
	Grips	Whyte Lock-on V Grip
✓	Front Brakes	TRP Slate, 4 Pot with Metal Sintered Pads, 180mm Rotor
✓	Rear Brakes	TRP Slate, 4 Pot with Metal Sintered Pads, 180mm Rotor
	Brake Levers	TRP Slate, I-Spec II
	Pedals	None
✓	Indicates an upgrade or improvement over previous version	
✓	Indicates an upgrade or improvement over the model below	

The award-winning second generation T-130 platform is all about maximum fun, wherever you ride. Combining climbing efficiency with a hooligan attitude to descents, it uses every bit of its 130mm of suspension travel to keep you grinning from ear to ear.

The T-130 OTO geometry was designed around a shorter 37mm offset fork. The extra front end grip this creates allows us to make the most of the 140mm travel fork, fully exploiting the capabilities of the chassis, the more neutral handling and the 2.6" tyres.

The SR is our most affordable spec, combining Fox Performance suspension with a Shimano based 11 speed drive-train - the result is a massively capable bike for an affordable price.

Dropout Code	DROPWH21
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	65.6	75	554	330	788
S	65.6	75	583	330	769
M	65.6	75	612	330	802
L	65.6	75	640	330	808
XL	65.6	75	669	330	815
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1118	430	30.9	100	368.3
S	1099	430	30.9	112	406.4
M	1132	430	30.9	125	431.8
L	1138	430	30.9	140	457.2
XL	1145	430	30.9	150	482.6

T-130 SR

T-130 Trail Suspension - 130mm

SRP £2,299

Product Code - WT130SR(size)V2

ADDITIONAL SPECIFICATION & REPLACEMENT PARTS

Top Tube	6061 Hydro Formed
Down Tube	6061 Triple Butted Hydro Formed
Rear Stays	6061 Alloy Double Butted
Paint Code	WAMTU011
Freehub Part Code	WHYFHUB01
Rear Hub Bearings	6903
Front Hub Bearings	6902
Suspension Bearings	WB0025 X 10
Headset Bearings	HS002 (FSA No57)
Headset Code	
Bottom Bracket	BSA Shimano Hollowtech 2, 73mm
ISG Chainguide Compatibility	
ICR Grommets	1 x WHYICR04, 2 x WHYICR02
Brake Mount Adaptor	WHYFM180
Spoke Lengths	276 x 274mm (front) 275 x 274mm (rear)
Max Chain Ring Size	36T
Chain Length for the stock chainring	116
Tubeless Status	Tubeless Ready Rims
Max Tyre Size	27.5 X 2.8 Front / 27.5 X 2.6 Rear
Max Tyre Size with Mudguards	N/A
Mudguard Code	N/A
Rack Compatible	N/A
Kickstand Compatible	N/A
Chain Guide Code	WAMCG1
Rear Thru-Axle Length	M12 X 1.5, 180mm Long
Downtube Protector	N/A
Chainstay Protector	WHYPRO07
Seat Post Seal	WHYPOSTSEAL
Kitbox Contents	