

T-130 S

T-130 Trail Suspension - 130mm

SRP £2,499

Product Code - WT130S(size)V2



		Colour	Matt Midnight with Ocean / Rose
		Sizes Available	XS,S,M,L,XL
		Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
✓	✓	Fork	RockShox Pike Select RC 27.5", 140mm Travel, 37mm Offset, DebonAir, Charger RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
✓		Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
		Headset	FSA No. 57 Orbit ZS, ACB, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
		Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, XD Driver, 32 Hole
✓	✓	Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 31mm Torque Caps, 32 Hole
		Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
✓		Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
		Tyres	Maxxis High Roller II TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.6" 60TPI, EXO Sidewall Protection, Rear
		Shift Levers	SRAM GX Eagle, MMX Clamp, 12 Speed
		Front Derailleur	N/A
		Rear Derailleur	SRAM GX Eagle, 12 Speed
	✓	Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed
	✓	Chain	SRAM Eagle, 12 Speed
	✓	Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
	✓	Bottom Bracket	SRAM DUB, BSA, 73mm
✓	✓	Seatpost	KS RAGEi, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Southpaw-Alloy Remote Lever
		Seat	Whyte Custom, Dual Density, Triple Panel Design
✓		Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS/S 760mm Wide, 15mm Rise, M/L/XL 780mm Wide, 30mm Rise
		Stem	Whyte Gravity Stem, 35mm Extension
		Grips	Whyte Lock-on V Grip
✓	✓	Front Brakes	SRAM Guide T, 4 Pot, 180mm Rotor
✓	✓	Rear Brakes	SRAM Guide T, 4 Pot, 180mm Rotor, Internal Routing
	✓	Brake Levers	SRAM Guide T, Matchmaker
		Pedals	None
✓		Indicates an upgrade or improvement over previous version	
	✓	Indicates an upgrade or improvement over the model below	

The award-winning second generation T-130 platform is all about maximum fun, wherever you ride. Combining climbing efficiency with a hooligan attitude to descents, it uses every bit of its 130mm of suspension travel to keep you grinning from ear to ear.

The T-130 OTO geometry was designed around a shorter 37mm offset fork. The extra front end grip this creates allows us to make the most of the 140mm travel fork, fully exploiting the capabilities of the chassis, the more neutral handling and the 2.6" tyres.

The Eagle groupset is fitted to the T-130 giving it all the benefits of their massive 480% gear range and allowing Whyte to increase the chain ring size without sacrificing the lower gearing size.

Dropout Code	DROPWH18
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	65.6	75	554	330	788
S	65.6	75	583	330	769
M	65.6	75	612	330	802
L	65.6	75	640	330	808
XL	65.6	75	669	330	815
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1118	430	30.9	100	368.3
S	1099	430	30.9	112	406.4
M	1132	430	30.9	125	431.8
L	1138	430	30.9	140	457.2
XL	1145	430	30.9	150	482.6

T-130 S

T-130 Trail Suspension - 130mm

SRP £2,499

Product Code - WT130S(size)V2

ADDITIONAL SPECIFICATION & REPLACEMENT PARTS

Top Tube	6061 Hydro Formed
Down Tube	6061 Triple Butted Hydro Formed
Rear Stays	6061 Alloy Double Butted
Paint Code	WAMTU012
Freehub Part Code	WHYFHUB01
Rear Hub Bearings	6903
Front Hub Bearings	6902
Suspension Bearings	WB0025 X 10
Headset Bearings	HS002 (FSA No57)
Headset Code	
Bottom Bracket	BSA SRAM DUB, 73mm
ISG Chainguide Compatibility	
ICR Grommets	1 x WHYICR04, 2 x WHYICR02
Brake Mount Adaptor	WHYFM180
Spoke Lengths	278 x 274mm (front) 294 x 292mm (rear)
Max Chain Ring Size	36T
Chain Length for the stock chainring	116
Tubeless Status	Tubeless Ready Rims
Max Tyre Size	27.5 X 2.8 Front / 27.5 X 2.6 Rear
Max Tyre Size with Mudguards	N/A
Mudguard Code	N/A
Rack Compatible	N/A
Kickstand Compatible	N/A
Chain Guide Code	WAMCG1
Rear Thru-Axle Length	M12 X 1.5, 180mm Long
Downtube Protector	N/A
Chainstay Protector	WHYPRO07
Seat Post Seal	WHYPOSTSEAL
Kitbox Contents	